

TECHNICAL DATA SHEET
MATTING PASTEThe identification code: E-PM
Line: EXLAK**PRODUCT DESCRIPTION**

This is a special additive to paints, allowing tarnishing of paint and obtain surface "without gloss". This effect is obtained by mixing the mating paste with any kind of paint in order to obtain the surface "without gloss".

USAGE

- universal matting paste for one- and two-component products

MIXING RATIO

Type of substance	Recommended amount of matting paste for 1L tarnishing substance		Loss of gloss levels
Cellulose topcoat	100-250 g	10-25%	About 50% (after adding 250 g of matting paste)
Synthetic topcoat	100-350 g	10-35%	About 50% (after adding 350 g of matting paste)
Polyurethane high gloss paint	100-400 g	10-40%	About 50% (after adding 400 g of matting paste)
Synthetic paint intended to heating (120°C)	100-250 g	10-25%	About 50% (after adding 250 g of matting paste)
Comments:	Amount of matting paste depends on the expected level of "tarnishing" of the surface.		
	Stir thoroughly before use (2-3 minutes).		

STORAGE TIME AND CONDITIONS

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 12 months from date of manufacture - date on the top of container.

HEALTH AND SAFETY REGULATIONS

See Safety Data Sheet of the product.