

TECHNICAL DATA SHEET

PRIMER PLASTIC


The identification code: E-PP
Line: EXLAK

PRODUCT DESCRIPTION

One-component colourless primer for application by brush or spray gun on car body parts made of plastic. In Car Refinish used as a primer coating and forming micro coating to obtain good adhesion topcoat to plastic.

APPLICATION

Ready for use. Designed for application by brush or spray gun.

	Number of layers	2	
	Pressure	2 - 2,5 bar	
	Nozzle	1.3 - 1.4 mm	
	Flash off between layers: 20 min		Operating hardness: 30-40 min at 20°C

After 30-40 min since applying the last layer of primer plastic, can be applied every type of topcoat.

CONTENT OF VOLATILE ORGANIC COMPOUNDS

Maximum content of VOC in product	810 g/l
VOC for category: II,B/e	840 g/l

Product complies standards of EU Directive 2004/42/CE/II,B/e(840)

STORAGE TIME AND CONDITIONS

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 12 months from date of manufacture - date on the top of container.

CLEANING EQUIPMENT

For cleaning equipment can be used acryl thinner [code: E-RA] or nitro thinner [code: E-RN]. It is recommended to use thinner for cleaning paint spray guns EXLAK [code: E-RDMP].

HEALTH AND SAFETY REGULATIONS

See Safety Data Sheet of the product.

SPECIFIC WEIGHT

About 0.9 g/cm³